

Wet Test System for High Voltage Devices - Type HSR

Instruction Manual

The contents complies with the requirements of DIN EN ISO/IEC 17025 - Cl. 5.4.1 as instruction on the use and operation of the device for wet tests according to the standards IEC 60060-1 and IEEE Std. 4

Table of Contents		Page
1	Product Description	3
2	Intended Use	3
3	Safety - Risks and Safety Precautions	3
3.1	Supply Voltage	3
3.2	High Voltage for Test	3
3.3	Transport of the Device in Ready-to-Use Condition	3
4	Requirements for Wet Tests acc. IEC 60060-1 and IEEE Std. 4	4
4.1	Precipitation Range, Water Characteristics, Pre-Wetting and Test Duration	4
4.2	Requirements for Passing the Test	4
5	Pre-Adjustment of Nozzle Distance, Spacing, Angle and Pressure Stage	5
5.1	Precipitation Range acc. IEC 60060-1	5
5.2	Precipitation Range acc. IEEE Std. 4	5
6	Handling and Operation	6
6.1	Set Up - Operational Position	6
6.2	Grounding Connection to the System of the Test Laboratory	6
6.3	Telescopic Mast for the Nozzles - Adjustment	6
6.4	Power Supply Connection	6
6.5	Pump feeding by Integrated or External Tank	7
6.6	Pressure Generation and Controll	7
6.7	Precipitation Procedure	8
7	Measurement of the Precipitation Rates with the Collecting Vessel	9
7.1	Collecting Procedure according IEC 60060-1, IEEE Std. 4	9
8	Conductivity and Temperature of the Water	10
8.1	Temperature of the Water - Measurement acc. Standard	10
8.2	Conductivity Reference Temperature and Temperature of the Water	10
8.3	Conductivity Meters without/with Temperature Compensated Indication	11
8.4	Conductivity of the Water - Adjustment	12
9	Atmospheric Correction Factors for External Insulation	12
10	Pre-Wetting and Test	13
11	Technical Data	14
12	Maintenance and Repetition of Electric Tests acc. DGUV 3 (BGV A3)	15
13	Storage und Transport	16
14	EU Directives and Standards for Production, Testing and Operation	16
Appendix		
1	Circuit Drawing for Pump Operation and Pressure Controll System	
2	Test Report of the Electric System	
3	EU Declaration of Conformity for the Installed Components	

11 Technical Data

Type:	HSR 500
Power supply:	2P+E, IEC 60309
Rated voltage:	230 V, 50 Hz
Overcurrent protection of power supply:	16 A
Integrated overcurrent protection:	10 A Type B
Rated current:	4 A
Integrated RCD:	30 mA
Overtemperature protection of the pump:	Thermoswitch
Electric protection class:	Pump CI I, Control box CI II isolated
Degree of protection:	IP 44, IEC 60529
Rated pressure:	0.8...3.0 bar _{rel} , max. 5.0 bar _{rel}
Volume of the tank:	500 l
Duration of precipitation:	90 min (IEC 60060-1, 500 l, 8 Nozzles)
External water supply:	3/4" IG
Filter in front of pump meshsize:	0.50 mm
Filter in front of nozzles meshsize:	0.16 mm
Torque for rack connections:	30 Nm
Size for transport L x W x H:	155 x 90 x 195 cm
Size for operation L x W x H:	155 x 140 x 550...1100 cm
	Mast and side beam removeable
Weight:	160 kg